

POWERED BY Dialog

Printing ink for forming silver conductor circuit - comprises resin of (modified) alkyd, fatty acid base polyepoxy resin, urethanated oil, rosin and maleic oil, silver flake powder, organosilver cpd., flux and solvents etc.

Patent Assignee: TANAKA KIKINZOKU KOGYO KK

Patent Family

Patent Number	Kind	Date	Application Number	Kind	Date	Week	Type
JP 5311103	A	19931122	JP 92146554	A	19920512	199351	B

Priority Applications (Number Kind Date): JP 92146554 A (19920512)

Patent Details

Patent	Kind	Language	Page	Main IPC	Filing Notes
JP 5311103	A		5	C09D-011/02	

Abstract:

JP 5311103 A

The printing ink comprises (A) at least one resin component selected from alkyd, modified alkyd, fatty acid base epoxy resins, urethanated oil, resin and maleic oil; (B) Ag component, pref. 0.05-1.0 micron dia. spherical powder and/or 0.5-5 micron flaky powder and Ag contg. organic metal cpd., pref. Ag carboxylate, Ag acetylacetonate or Ag alkoxide, and/or Ag contg. colloid; (C) flux component, pref. organic metal cpd. and/or glass frit and opt. (D) one or more than two components selected from solvent, leveling agent, polymerisation initiator, oxidn. promoter, anti-skinning agent, thickening agent, metal chelating resin, dispersant and filler. Forming Ag conductor circuits comprises (I) offset printing circuit patterns on a substrate using ink for forming Ag conductor circuits; opt. (I') pressing the printed circuit patterns to make their surfaces flat and smooth; (II) curing the printed patterns by as they are/or by irradiation of active energy radiation, pref. at least one selected from UV, IR and electron rays and/or by heating; (III) overprinting the cured circuit patterns as they are and/or by the same pattern; and (IV) calcining the printed patterns, pref. at a temp. above 300 deg. C is also new.

USE/ADVANTAGE - The printing ink for forming Ag conductor circuits and the method for forming Ag conductor circuits using the printing ink are suitable for forming Ag conductor circuits on various substrates which are used in various fields of the electronic industry. The obtd. printed Ag conductor circuits have good surface flatness due to good leveling properties, fine patterns having no defects e.g. wire breaking and reduced resistivity.

Dwg.0/0

Derwent World Patents Index

© 2004 Derwent Information Ltd. All rights reserved.

Dialog® File Number 351 Accession Number 9717509

Basic Patent (Number,Kind,Date): JP 7136194 A2 950530

PATENT FAMILY:

Japan (JP)

Patent (Number,Kind,Date): JP 7136194 A2 950530
DRAIN TRAP AID DEVICE (English)
Patent Assignee: MORITA TOKYO SEISAKUSHO KK
Author (Inventor): KADOMA SHIGEYUKI
Priority (Number,Kind,Date): JP 93311103 A 931118
Applic (Number,Kind,Date): JP 93311103 A 931118
IPC: * A61C-017/00
Language of Document: Japanese

INPADOC/Family and Legal Status

© 2004 European Patent Office. All rights reserved.

Dialog® File Number 345 Accession Number 12423923

Basic Patent (Number,Kind,Date): JP 5311103 A2 931122

PATENT FAMILY:

Japan (JP)

Patent (Number,Kind,Date): JP 5311103 A2 931122
PRINTING INK FOR SILVER CONDUCTOR CIRCUIT AND METHOD FOR FORMING
SILVER CONDUCTOR CIRCUIT (English)
Patent Assignee: TANAKA PRECIOUS METAL IND
Author (Inventor): OKUDA AKIHIKO
Priority (Number,Kind,Date): JP 92146554 A 920512
Applic (Number,Kind,Date): JP 92146554 A 920512
IPC: * C09D-011/02; C09D-005/24; H05K-001/09; H05K-003/12
CA Abstract No: ; 120(18)220580A
Derwent WPI Acc No: ; C 93-411062
JAPIO Reference No: ; 180122C000157
Language of Document: Japanese

INPADOC/Family and Legal Status

© 2004 European Patent Office. All rights reserved.

Dialog® File Number 345 Accession Number 11493110

Basic Patent (Number,Kind,Date): JP 54103738 A2 790815

PATENT FAMILY:

Japan (JP)

Patent (Number,Kind,Date): JP 54103738 A2 790815
PRESERVING OF VACUUM MOLDING CORE (English)
Patent Assignee: SINTOKOGIO LTD
Author (Inventor): TOMONAGA JIYUNICHI; SUGIURA HAJIME; MAKIGUCHI TADASHI
Priority (Number,Kind,Date): JP 7811103 A 780202
Applic (Number,Kind,Date): JP 7811103 A 780202
IPC: * B22C-009/02
Language of Document: Japanese

INPADOC/Family and Legal Status

© 2004 European Patent Office. All rights reserved.

Dialog® File Number 345 Accession Number 2821572

Basic Patent (Number,Kind,Date): JP 53011103 A2 780201

PATENT FAMILY:**Japan (JP)**

Patent (Number,Kind,Date): JP 53011103 A2 780201
SLAG REMOVING METHOD (English)
Patent Assignee: KOBE STEEL LTD
Author (Inventor): HARAGUCHI TOSHIO; TAKAHATA SHINICHI; HIDAISHI TAIZOU;
NAKANO SHIGERU; SUGAWARA HIROFUMI
Priority (Number,Kind,Date): JP 7685529 A 760716
Applic (Number,Kind,Date): JP 7685529 A 760716
IPC: * C22B-009/00; B22D-043/00; F27D-003/15
JAPIO Reference No: * 020052C000236
Language of Document: Japanese
Patent (Number,Kind,Date): JP 81031500 B4 810722
Priority (Number,Kind,Date): JP 7685529 A 760716
Applic (Number,Kind,Date): JP 7685529 A 760716
IPC: * F27D-003/15; B22D-043/00
Language of Document: Japanese

INPADOC/Family and Legal Status

© 2004 European Patent Office. All rights reserved.

Dialog® File Number 345 Accession Number 2313603

Basic Patent (Number,Kind,Date): JP 51003077 A2 760112

PATENT FAMILY:**Japan (JP)**

Patent (Number,Kind,Date): JP 51003077 A2 760112
PEEPAAKATSUTAA (English)
Patent Assignee: COPAL CO LTD

Author (Inventor): HASEGAWA TSUNEE; SATO HIROYUKI
Priority (Number,Kind,Date): JP 7472141 A 740624
Applic (Number,Kind,Date): JP 7472141 A 740624
IPC: * B26D-001/06; B23D-015/04
Language of Document: Japanese
Patent (Number,Kind,Date): JP 78011103 B4 780419
Priority (Number,Kind,Date): JP 7472141 A 740624
Applic (Number,Kind,Date): JP 7472141 A 740624
IPC: * B26D-007/26
Language of Document: Japanese